



Specifications

- Current Rating: 1 Amps
- Insulator Resistance: 1000 Megohms min.
- Contact Resistance: 20 m ohms max.
- Dielectric Withstanding: AC 300V
- Operating Temperature : -55°C ~ +125°C
- Contact Material: Phosphor Bronze
- Insulator Material: Polyester, UL 94V-0, LCP
- Contact Plated: See Option / Standard = Full Gold Flash

Part Numbering System

FH7-SD-343124 - XX - X X L

- Series _____
- No. of Pins _____
- Contact Plating _____
- Packing Method: _____
B = Tube
- Insulator Material: _____
L = LCP



| * Contact Plating Option | Full Gold Plating | Gold Plated On Contact Area Tin Plated on Solder Area | Full Tin Plating |
|--------------------------|--|---|------------------|
| | G : Gold Flash G10: Gold 10u" G15: Gold 15u" G30: Gold 30u" | S: Gold Flash S10: Gold 10u" S15: Gold 15u" S30: Gold 30u" | T: Tin 100u" |

| General Tolerance | |
|-------------------|-----------|
| X. ± 0.50 | X.° ± 5° |
| .X ± 0.20 | .X° ± 2° |
| .XX ± 0.10 | .XX° ± 1° |
| Units : mm | |