




Recommended P.C. Board SMD Layout



A Type



B Type



Specifications

- Current Rating: 1 Amps
- Insulator Resistance: 1000 Megohms min.
- Contact Resistance: 20 m ohms max.
- Dielectric Withstanding: AC 300V
- Operating Temperature : -40°C ~ +125°C
- Contact Material: Phosphor Bronze
- Insulator Material: Polyester, UL 94V-0, Nylon-6T
- Contact Plated: See Option / Standard = Full Gold Flash

Part Numbering System

FH7C-SS-202132 - X XX - X X X N

- Series** _____
- Pin Layout Type:** _____
 A = A Type
 B = B Type
- No. of Pins** _____
- Contact Plating** _____
- Cap Option:** _____
 Nil = No Cap
 F = Film
 M = Metal Cap
 P = Plastic Cap
- Packing Method:** _____
 B = Tube
 T = Tape and Reel
- Insulator Material:** _____
 N = High Temperature Nylon-6T

* Contact Plating Option	Full Gold Plating	Gold Plated On Contact Area Tin Plated on Solder Area	Full Tin Plating
	G : Gold Flash G10: Gold 10u" G15: Gold 15u" G30: Gold 30u"	S: Gold Flash S10: Gold 10u" S15: Gold 15u" S30: Gold 30u"	T: Tin 100u"

General Tolerance	
X. ± 0.50	X.° $\pm 5^\circ$
.X ± 0.20	.X° $\pm 2^\circ$
.XX ± 0.10	.XX° $\pm 1^\circ$
Units : mm	